



# Saylite



AmberLED  
Turtle Friendly  
Solutions

**Lighting  
done right.**

# AmberLED Area & Wall Lights

The LEPG AmberLED KH15Q luminaire is available in two wattages with horizontal cut-off mounting configurations and a shielded IES Type V distribution, and is certified by the Florida Fish & Wildlife Conservation Commission (FWC) for wildlife applications that are directly visible from the shore requiring monochromatic AMBER light.

- **Wattage:**
  - 22w: Array: 22w, System: 25.4w; (Up to 100w HID Equivalent.)
  - 37w: Array: 37w, System: 38.2w; (Up to 175w HID Equivalent.)
- **Housing:**
  - Die Cast Aluminum Housing and Front Frame, Integral Heat Sinking and Driver Compartment. Photocell Adaptable. Nickel-Plated Stainless Steel Hardware. Includes Full Baffle Required to Maintain FWC Certification.
- **Listing & Ratings:**
  - CSA: Listed for Wet Locations, ANSI/UL 1598, 8750; IP66 Sealed LED Compartment.
- **Finish:**
  - Textured Architectural Bronze Powdercoat Finish Over a Chromate Conversion Coating. Custom Colors Available Upon Request.
- **Lens:**
  - Tempered Clear Flat Glass Lens
- **Mounting Options:**
  - Mounts with Kitty Hawk Arm, 2 $\frac{3}{8}$ " Diameter Mounting Arm Adapter, or Easy Hang Wall Bracket (Factory Installed).



# AmberLED Area & Wall Lights

The LEPG AmberLED KH25Q luminaire is available with horizontal cut-off mounting configurations and a shielded IES Type V distribution, and is certified by the Florida Fish & Wildlife Conservation Commission (FWC) for wildlife applications that are directly visible from the shore requiring monochromatic AMBER light.

- **Wattage:**
  - Array: 81w, System: 81.5w; (150-250w HID Equivalent.)
- **Housing:**
  - Die Cast Aluminum Housing and Front Frame, Integral Heat Sinking and Driver Compartment. Photocell Adaptable. Nickel-Plated Stainless Steel Hardware. Includes Full Baffle Required to Maintain FWC Certification.
- **Listing & Ratings:**
  - CSA: Listed for Wet Locations, ANSI/UL 1598, 8750; IP66 Sealed LED Compartment.
- **Finish:**
  - Textured Architectural Bronze Powdercoat Finish Over a Chromate Conversion Coating. Custom Colors Available Upon Request.
- **Lens:**
  - Tempered Clear Flat Glass Lens
- **Mounting Options:**
  - Mounts with Kitty Hawk Arm, 2 $\frac{3}{8}$ " Diameter Mounting Arm Adapter, or Easy Hang Wall Bracket (Factory Installed).





# AmberLED Garage Lighter

The LEPG AmberLED VN55Q luminaire is available with a shielded IES Type V distribution, and is certified by the Florida Fish & Wildlife Conservation Commission (FWC) for wildlife applications that are directly visible from the shore requiring monochromatic AMBER light.

- **Wattage:**
  - 39w: Array: 39w, System: 43.4w;
  - 52w: Array: 52w, System: 57.2w; (Up to 175w HID Equivalent)
- **Housing:**
  - Low Profile Die Cast Aluminum Housing, ½" Coin Plugs with O-rings for Conduit or External Sensor. Built-in Sensor Housing with Color-Matched UV-Stabilized Polycarbonate Cover. A Clear Cover will be Provided When a Sensor is Ordered. Includes Full Baffle Required to Maintain FWC Certification.
- **Listing & Ratings:**
  - CSA: Listed for Wet Locations, ANSI/UL 1598, 8750; IP66 Sealed LED Compartment.
- **Finish:**
  - Textured Architectural Bronze Powdercoat Finish Over a Chromate Conversion Coating. Custom Colors Available Upon Request.
- **Lens:**
  - Molded UV-Stabilized Acrylic Optical Lens Designed for Garage Lighting Applications.
- **Mounting Options:**
  - Included Easy-Hang Bracket Fits Standard 4" Electrical Box, Allowing One-Person Installation. Optional Quick-Mount/Pendant Bracket Available.



# AmberLED Wall Accent Light

The LEPG AmberLED TV2 C3 Full Cut-off wall mount luminaire is available with a shielded IES Type II distribution, and is certified by the Florida Fish & Wildlife Conservation Commission (FWC) for wildlife applications that are directly visible from the shore requiring monochromatic AMBER light.

- Wattage:
  - COB 40w, System Input 43w; (175w HID Equivalent)
- Housing:
  - Die-Cast Gasketed Aluminum Housing, Includes Cast-In Box Template and Built in Level. White Reflector. Nickel-Plated Stainless Steel Hardware. Includes Full Baffle Required to Maintain FWC Certification.
- Listing & Ratings:
  - CSA: Listed for Wet Locations, ANSI/UL 1598, 8750; IP65 Sealed LED Compartment.
- Finish:
  - Textured Architectural Bronze Powdercoat Finish Over a Chromate Conversion Coating. Custom Colors Available Upon Request.
- Lens:
  - Tempered Clear Flat Glass Lens.
- Mounting Options:
  - Mount Directly Over Recessed Electrical Box or Use ½" Surface Conduit.



# AmberLED Wall Cylinder

The LEPG AmberLED WCTRS C3 Turbine Full Cut-off wall mount cylinder is available with a shielded IES Type V distribution, and is certified by the Florida Fish & Wildlife Conservation Commission (FWC) for wildlife applications that are directly visible from the shore requiring monochromatic AMBER light

- Wattage:
  - COB 20w, System Input 21w; (100w HID Equivalent)
- Housing:
  - Extruded Round Aluminum Housing with Built-in Heat Sinks. Includes Visor Required to Maintain FWC Certification.
- Listing & Ratings:
  - CSA: Listed for Wet Locations, ANSI/UL 1598, 8750; IP66 Sealed LED Compartment.
- Finish:
  - Textured Architectural Bronze or Black Powdercoat Finish Over a Chromate Conversion Coating. Custom Colors Available Upon Request.
- Lens:
  - Tempered Clear Flat Glass Lens.
- Mounting Options:
  - Mount Over a 4" Recessed Outlet Box.



# AmberLED Small Full Cutoff Wall Pack

The LEPG AmberLED WPC12Q Full Cut-off wall mount luminaire is available with a shielded IES Type V distribution, and is certified by the Florida Fish & Wildlife Conservation Commission (FWC) for wildlife applications that are directly visible from the shore requiring monochromatic AMBER light

- Wattage:
  - Array: 22w, System: 24.8w; (175w HID Equivalent)
- Housing:
  - Die Cast Hinged and Gasketed Aluminum Front Frame and Housing with ½" Coin Plugs. Nickel-Plated Stainless Steel Hardware. Photocell Adaptable. Includes Full Baffle Required to Maintain FWC Certification.
- Listing & Ratings:
  - CSA: Listed for Wet Locations, ANSI/UL 1598, 8750; IP65 Sealed LED Compartment.
- Finish:
  - Textured Architectural Bronze or Black Powdercoat Finish Over a Chromate Conversion Coating. Custom Colors Available Upon Request.
- Lens:
  - Tempered Clear Flat Glass Lens.
- Mounting Options:
  - Cast-in Template for Mounting Directly Over a 4" Recessed Outlet Box, or Use ½" Surface Conduit.



# AmberLED Medium Full Cutoff Wall Pack

The LEPG AmberLED WPC15Q Full Cut-off wall mount luminaire is available with a shielded IES Type V distribution, and is certified by the Florida Fish & Wildlife Conservation Commission (FWC) for wildlife applications that are directly visible from the shore requiring monochromatic AMBER light

- Wattage:
  - Array: 37w, System: 40w; (250w HID Equivalent)
- Housing:
  - Die Cast Hinged and Gasketed Aluminum Front Frame and Housing with ½" Coin Plugs. Nickel-Plated Stainless Steel Hardware. Photocell Adaptable. Includes Full Baffle Required to Maintain FWC Certification.
- Listing & Ratings:
  - CSA: Listed for Wet Locations, ANSI/UL 1598, 8750; IP65 Sealed LED Compartment.
- Finish:
  - Textured Architectural Bronze or Black Powdercoat Finish Over a Chromate Conversion Coating. Custom Colors Available Upon Request.
- Lens:
  - Tempered Clear Flat Glass Lens.
- Mounting Options:
  - Cast-in Template for Mounting Directly Over a 4" Recessed Outlet Box, or Use ½" Surface Conduit.





# AmberLED Vaporproof Straight Shade

The LEPG AmberLED LEDicated Vaporproof pendant and ceiling mount fixtures with straight shades are available with a shielded IES Type V distribution, and are certified by the Florida Fish & Wildlife Conservation Commission (FWC) for wildlife applications that are directly visible from the shore requiring monochromatic AMBER light

- Wattage:
  - Array: 22w, System: 27w; (175w HID Equivalent)
- Housing:
  - Heavy Duty Die Cast Aluminum Housing with Integral Heat Sinking, ¾" NPS Threaded Mounts. Includes Shade Required to Maintain FWC Certification.
- Listing & Ratings:
  - CSA: Listed for Wet Locations, ANSI/UL 1598, 8750; IP66 Sealed LED Compartment.
- Finish:
  - Smooth Powdercoat Finish Over a Chromate Conversion Coating. Custom Colors Available Upon Request.
- Lens:
  - Flat Clear Tempered Glass Lens
- Mounting Options:
  - Pendant Mount or Surface Mount on Ceiling.



# AmberLED Vaporproof Angled Shade

The LEPG AmberLED LEDicated Vaporproof pendant, wall and ceiling mount fixtures with angled shades are available with a shielded IES Type V distribution, and are certified by the Florida Fish & Wildlife Conservation Commission (FWC) for wildlife applications that are directly visible from the shore requiring monochromatic AMBER light.

- Wattage:
  - Array: 22w, System: 27w (175w HID Equivalent)
- Housing:
  - Heavy Duty Die Cast Aluminum Housing with Integral Heat Sinking, ¾" NPS Threaded Mounts. Includes Shade Required to Maintain FWC Certification.
- Listing & Ratings:
  - CSA: Listed for Wet Locations, ANSI/UL 1598, 8750; IP66 Sealed LED Compartment.
- Finish:
  - Smooth Powdercoat Finish Over a Chromate Conversion Coating. Custom Colors Available Upon Request.
- Lens:
  - Flat Clear Tempered Glass Lens
- Mounting Options:
  - Pendant Mount or Surface Mount on Wall or Ceiling



# AmberLED Round Dome Bollards w/ Louvers

The LEPG AmberLED Round Dome Top Bollards are available with cone reflector or louvers with 270° glare shield, and are certified by the Florida Fish & Wildlife Conservation Commission (FWC) for wildlife applications that are directly visible from the shore requiring monochromatic AMBER light.

- Wattage:
  - Array: 14.5w, System: 17w; (70w HID Equivalent)
- Housing:
  - Extruded Aluminum Housing with Flush Mounting Base & Vandal-Resistant Screws, Domed Top, Internal Ballast Tray for Easy Maintenance. Includes 270° Shield Required to Maintain FWC Certification. Bollards Can Be Cut to Custom Lengths Upon Request.
- Listing & Ratings:
  - CSA: Listed for Wet Locations, ANSI/UL 1598, 8750; IP65 Sealed LED Compartment.
- Finish:
  - Textured Architectural Bronze or Black Powdercoat Finish Over a Chromate Conversion Coating. Custom Colors Available Upon Request
- Lens:
  - Clear UV-Stabilized Polycarbonate Vandal-Resistant Lens
- Mounting Options:
  - Mounting Kit with 8" Zinc-Plated Anchor Bolts, Included.



# AmberLED Round Dome Bollards w/ Cone Reflector

The LEPG AmberLED Round Dome Top Bollards are available with cone reflector or louvers with 270° glare shield, and are certified by the Florida Fish & Wildlife Conservation Commission (FWC) for wildlife applications that are directly visible from the shore requiring monochromatic AMBER light.

- Wattage:
  - Array: 14.5w, System: 17w; (70w HID Equivalent)
- Housing:
  - Extruded Aluminum Housing with Flush Mounting Base & Vandal-Resistant Screws, Domed Top, Internal Ballast Tray for Easy Maintenance. Includes 270° Shield Required to Maintain FWC Certification. Bollards Can Be Cut to Custom Lengths Upon Request.
- Listing & Ratings:
  - CSA: Listed for Wet Locations, ANSI/UL 1598, 8750; IP65 Sealed LED Compartment.
- Finish:
  - Textured Architectural Bronze or Black Powdercoat Finish Over a Chromate Conversion Coating. Custom Colors Available Upon Request
- Lens:
  - Clear UV-Stabilized Polycarbonate Vandal-Resistant Lens
- Mounting Options:
  - Mounting Kit with 8" Zinc-Plated Anchor Bolts, Included.





# AmberLED Round Flat Bollard w/ Louvers

The LEPG AmberLED Round Flat Top Bollards are available with cone reflector or louvers with 270° glare shield, and are certified by the Florida Fish & Wildlife Conservation Commission (FWC) for wildlife applications that are directly visible from the shore requiring monochromatic AMBER light.

- Wattage:
  - Array: 14.5w, System: 17w; (70w HID Equivalent)
- Housing:
  - Extruded Aluminum Housing with Flush Mounting Base & Vandal-Resistant Screws, Domed Top, Internal Ballast Tray for Easy Maintenance. Includes 270° Shield Required to Maintain FWC Certification. Bollards Can Be Cut to Custom Lengths Upon Request.
- Listing & Ratings:
  - CSA: Listed for Wet Locations, ANSI/UL 1598, 8750; IP65 Sealed LED Compartment.
- Finish:
  - Textured Architectural Bronze or Black Powdercoat Finish Over a Chromate Conversion Coating. Custom Colors Available Upon Request
- Lens:
  - Clear UV-Stabilized Polycarbonate Vandal-Resistant Lens
- Mounting Options:
  - Mounting Kit with 8" Zinc-Plated Anchor Bolts, Included.



# AmberLED Round Flat Bollard w/ Cone Reflector

The LEPG AmberLED Round Flat Top Bollards are available with cone reflector or louvers with 270° glare shield, and are certified by the Florida Fish & Wildlife Conservation Commission (FWC) for wildlife applications that are directly visible from the shore requiring monochromatic AMBER light

- Wattage:
  - Array: 14.5w, System: 17w; (70w HID Equivalent)
- Housing:
  - Extruded Aluminum Housing with Flush Mounting Base & Vandal-Resistant Screws, Domed Top, Internal Ballast Tray for Easy Maintenance. Includes 270° Shield Required to Maintain FWC Certification. Bollards Can Be Cut to Custom Lengths Upon Request.
- Listing & Ratings:
  - CSA: Listed for Wet Locations, ANSI/UL 1598, 8750; IP65 Sealed LED Compartment.
- Finish:
  - Textured Architectural Bronze or Black Powdercoat Finish Over a Chromate Conversion Coating. Custom Colors Available Upon Request
- Lens:
  - Clear UV-Stabilized Polycarbonate Vandal-Resistant Lens
- Mounting Options:
  - Mounting Kit with 8" Zinc-Plated Anchor Bolts, Included.



# AmberLED Stainless Steel Bollard w/ Louvers

The LEPG AmberLED Bollards are available with cone reflector or louvers with 270° glare shield, and are certified by the Florida Fish & Wildlife Conservation Commission (FWC) for wildlife applications that are directly visible from the shore requiring monochromatic AMBER light.

- Wattage:
  - Array: 14.5w, System: 17w; (70w HID Equivalent)
- Housing:
  - Formed 316L Stainless Steel Housing with Flush Mounting Base & Vandal-Resistant Screws, Domed Top, Internal Ballast Tray for Easy Maintenance. Includes 270° Shield Required to Maintain FWC Certification.
- Listing & Ratings:
  - CSA: Listed for Wet Locations, ANSI/UL 1598, 8750; IP65 Sealed LED Compartment.
- Finish:
  - Stainless Steel
- Lens:
  - Clear UV-Stabilized Polycarbonate Vandal-Resistant Lens
- Mounting Options:
  - Mounting Kit with 8" Zinc-Plated Anchor Bolts, Included.



# AmberLED Stainless Steel Bollard w/ Cone Reflector

The LEPG AmberLED Bollards are available with cone reflector or louvers with 270° glare shield, and are certified by the Florida Fish & Wildlife Conservation Commission (FWC) for wildlife applications that are directly visible from the shore requiring monochromatic AMBER light

- Wattage:
  - Array: 14.5w, System: 17w; (70w HID Equivalent)
- Housing:
  - Formed 316L Stainless Steel Housing with Flush Mounting Base & Vandal-Resistant Screws, Domed Top, Internal Ballast Tray for Easy Maintenance. Includes 270° Shield Required to Maintain FWC Certification.
- Listing & Ratings:
  - CSA: Listed for Wet Locations, ANSI/UL 1598, 8750; IP65 Sealed LED Compartment.
- Finish:
  - Stainless Steel
- Lens:
  - Clear UV-Stabilized Polycarbonate Vandal-Resistant Lens
- Mounting Options:
  - Mounting Kit with 8" Zinc-Plated Anchor Bolts, Included.

